AY-Q6350

Anti- Vandal MIFARE® Contactless Smartcard Reader with Keypad



THIS ANTI-VANDAL MIFARE® 13.65 MHz SMARTCARD AND PIN CODE READER HAS AN ELEGANT DESIGN WITH BLUE BACKLIT KEYS. THE AY-Q6350 IS AN ADVANCED MODEL WITH MULTI-FORMAT OUTPUTS FOR HIGH COMPATIBILITY WITH STANDARD HOST ACCESS CONTROLLERS. IT HAS A LOCAL MENU TO PROGRAM FACILITY CODE AS WELL AS CARD & PIN CREDENTIAL MODES.

GENERAL DESCRIPTION

The AY-Q6350 is the latest addition to Rosslare's family of MIFARE® card readers. It can read Mifare® card serial number (CSN) from all ISO 14443A-3 type cards.

AY-Q6350 has locally programmable modes for 1-to 8-digit PIN codes, with a high-security option of "PIN plus card", as well as a 3-digit Facility code. Even with the unit's strong features, this reader is user-friendly and easy-to-install with an additional level of security in the form of a password-protected menu.

This reader supports Wiegand 26-, 32-, 34-, and 40-Bit or Clock & Data output protocols. It has a 6-wire shielded cable interface to the host controller for power, data, LED control input, and tamper status.

Backlight offers a higher level of user accessibility. This anti-vandal unit is ideal for installations where style, security and functionality are highly important.

MAIN FEATURES

- Incorporates the ISO-14443A (MIFARE®) ID Format Protocol
- Read range of up to 45 mm (1.8 in.)
- 8 programmable proximity card transmission formats, Wiegand 26- to 40-Bit or Clock & Data

- Blue backlit 3x4 keypad
- High strength design, epoxy potted, fully sealed within an all-metallic housing
- Selectable LED control or buzzer control functions
- Made from tough polycarbonate plastic for improved performance in all weather conditions

PROFESSIONAL GRADE FEATURES

- Optical tamper sensor for cover and wall tamper detection
- 8 programmable PIN transmission formats for data and credential entry options
- Card + PIN mode for higher security
- Door bell key feature (from "*" key when interfaced with Rosslare controllers)
- Water-resistant with epoxy potting (IP65) suitable for indoor and outdoor applications
- One tri-colored LED and integral sounder for programming and operation
- Programmable Facility code
- Installation kit includes template label, security screw, and tool
- 60 cm (23.6 in.) 6-wire interface cable



SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

| ELECTRICAL SPECIFICATIONS | |
|---|---|
| Operating Voltage Range | 5 to 16 VDC – from a linear type power supply (18 VDC is absolute maximum) |
| Standby Input Current | 115 mA |
| Maximum Input Current | 160 mA |
| ■ LED Control | Dry Contact, N.O. |
| Proximity Card Reader | Max. read range: 30 mm (1.18 in.) Operating Frequency: 13.56 MHz Compatible Cards: MIFARE® Compatible ISO-14443A |
| ■ Tamper Output | Open collector, active low, max. sink current 32 mA |
| OPERATIONAL SPECIFICATIONS | |
| Keypad | 3x4 blue backlit keys for PIN codes entry and local programming Door bell key ('*') function (with Rosslare controllers only) |
| Facility Code | Programmable |
| PIN Code Formats | 8 selectable formats, from single to 8-digit PIN codes |
| Card Output Formats | 8 selectable formats: Wiegand 26-Bit, with Facility code, 32-Bit, 32-Bit Reversed, 34-Bit, 40-Bit, Clock & Data and Wiegand Card + PIN |
| Indications and Sounds | Tri-colored LED, built-in sounder with selectable LED/sounder control input |
| ENVIRONMENTAL SPECIFICATIONS | |
| Operating Environment | Indoor and outdoor use (all weather) – meets IP65 |
| Operating Temperature | -31°C to 63°C (-25°F to 145° F) |
| Operating Humidity | 0% to 95% (non-condensing) |
| RFI Protection | > 20 V/m up to 1000 MHz |
| PHYSICAL SPECIFICATIONS | |
| Dimensions (H x W x D) | 120 x 76 x 22mm (4.72 x 3 x 0.97 in.) |
| ■ Weight | 440 g (0.97 lb) |
| SYSTEM COMPONENTS | The AY-Q6350 is compatible with a variety of Rosslare's controllers (AC-225, AC-215, AC-115, and so on), as well as with many third-party systems. In addition, it is compatible with Rosslare's AT-T511, AT-T521 and AT-T531 Ultralight (64 bytes), 1K and 4K MIFARE® cards. |
| PRODUCT WARRANTY | 5-Year Limited Product Warranty |
| | |

ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

www.rosslaresecurity.com

MIFARE® is a Trademark of NXP Semiconductors









