

PLUS

New generation control unit with LCD display.

New generation control unit with soft start and soft stop function availability.



Motor speed regulation and safety edge connection possibility.



CT-824S



CT-724S

CODE	DESCRIPTION
 CT-824S	For two motors, 24 Vdc switching with encoder, battery charger and connectors for receiver.
 CT-724S	For one sliding, overhead motor or barrier 24 Vdc, with encoder.

TECHNICAL DATA		CT-824S	CT-724S
power	Vac / Hz	230 / 50	24 / 50
output accessories power	Vdc / mA	24 / 400	24 / 300
working time	sec	2-180	2-180
protection degree	IP	54	54
operating temperature	° C	-20° + 55°	-20° + 55°

PLUS

Easy programming.

Encoder for the obstacle detection (CT-101).

New generation control unit with LCD display (CT-101 and CT-201).



CT-101



CT-2



CT-201



CT-1EBR

CODE	DESCRIPTION
CT-101	For one sliding, overhead or barrier 230 Vac motor. With electric clutch and connectors for receiver, encoder and slowdown in opening and closing.
CT-2	For two swing 230 Vac motors, with logical control card, with connectors for receiver. In box.
CT-201	For two swing 230 Vac motors, with electric clutch option, connectors for receiver and slowdown. In box.
CT-1EBR	For one rolling shutter motor 230 Vac. With electric clutch and radio decoder. Rolling code. In box.

TECHNICAL DATA		CT-101	CT-2	CT-201	CT-1EBR
power	Vac / Hz	230 / 50	230 / 50	230 / 50	230 / 50
output accessories power	Vdc / mA	24 / 300	24 / 400	24 / 400	24 / 300
working time	sec	120	60	120	2-60
pause time	sec	120	2-180	120	-
protection degree	IP	54	54	54	56
operating temperature	° C	-20° + 55°	-20° + 55°	-20° + 55°	-20° + 55°

For industrial motor.

With connectors for receiver.

400 Vac CONTROL UNITS



CT-380
CT-380E



CT-381
CT-381E

CODE	DESCRIPTION
CT-380	For one sliding or industrial sectional doors 400 Vac / 230 Vac motor, with slowdown, brake system, connection for receiver. In box.
CT-381	For one sliding or industrial sectional doors 400 Vac / 230 Vac motor, with slowdown, brake system, connection for receiver. In box with control buttons.
CT-380E	For one sliding or industrial sectional doors 400 Vac / 230 Vac motor, with connection for receiver. In box.
CT-381E	For one sliding or industrial sectional doors 400 Vac / 230 Vac motor, with connection for receiver. In box with control buttons.

TECHNICAL DATA		CT-380 / CT-381 CT-380E / CT-381E
power motore	Vac / Hz	400-230 / 50
max motor load	W	2000
output accessories power	Vdc / W	24 / 15
working time	sec	0-120
pause time	sec	0-120
protection degree	IP	56
operating temperature	° C	-20° + 55°

GO 24/GO 230/GO 380 ACCESSORIES

COMMON ACCESSORIES



RXI-22
2 channels plug-in receiver,
fix or rolling code.




RXM-22
2 channels universal receiver,
fix or rolling code. In box.

ACCESSORIES GO 24




BOXKEY
Plastic box for two motors
control unit.



KBPKN
Kit 24 Vdc batteries,
1300 mAh and battery
charger, up to 500 kg.



KITFIXBATT
Kit fixing batteries 24 Vdc
for **BOXKEY** (2 PCS).



KBPKN2
Kit 24 Vdc batteries, 10
A, 1300 mAh and battery
charger, from 500 kg for
extreme performance.



BAT-12-2A
Battery 12 V 2 A.

ACCESSORIES GO 230



460T230V101B
Transformer for **CT-101**.



BOXKEYS
Plastic box for one motor
control unit.