

# TURBO 30

ELECTROMECHANICAL GEAR MOTOR FOR SLIDING GATES  
UP TO 300 Kg, 24 Vdc



## PLUS



With slowdown function both in opening and closing to preserve gate integrity

Electronic and mechanical parts well protected from external agents

Easy maintenance thanks to the horizontal control unit position

With fixing plate included



Internal battery back-up optional



Hidden external case fixing



Compact dimensions



Magnetic limit switch

## MODELS

| CODE     | DESCRIPTION   | PCS PALLET |
|----------|---|------------|
| SC-30CSM | For sliding gates up to 300 Kg, 24 Vdc motor, control unit with slowdown and magnetic limit switch (1 pc) | 36         |

| TECHNICAL DATA         |           | SC-30CSM          |
|------------------------|-----------|-------------------|
| <b>MECHANICAL DATA</b> |           |                   |
| speed *                | cm/s      | 20                |
| torque                 | Nm        | 10                |
| working cycle          | %         | 50                |
| <b>ELECTRICAL DATA</b> |           |                   |
| control board          |           | CT-24M            |
| power                  | Vac (Vdc) | 230 (24)          |
| motor consumption      | A         | 1,1               |
| absorbed power         | W         | 250               |
| <b>GENERIC DATA</b>    |           |                   |
| protection degree      | IP        | 54                |
| dimensions (L - P - H) | mm        | 253 - 170,5 - 240 |
| weight                 | kg        | 9                 |
| working temperature    | °C        | -20 + 55          |
| gate maximum weight    | Kg        | 300               |

\* variable according to the gate weight

## ACCESSORIES



**BAT-12**  
Battery 12 V 1.3 A

PC1



**CABAT-30**  
Battery charger for 24 Vdc motors

PC 1



**RXI23X**  
2 channels plug-in receiver, fix or rolling code

PC 1



**CREM-P**  
M4 nylon toothed rack L=1000 mm for gates up to max 800 kg

PC 1



**TS**  
Warning board

PC 1