

### ELECTROMECHANICAL GEAR MOTOR FOR SWING GATES WITH LEAVES UP TO 4 m, 24 Vdc AND 230 Vac



# 

Built in LED light in the frontal part of motor body, to light up gate entrance and define width of the passage at night

High technological materials resistant to weather conditions

UV-resistant plastic covers

Extremely silent mechanics, protected by robust die-casted and powder-coated aluminum body

Alligned front and rear mounting brackets to ease motors installation

Manual unlock possible with Sub transmitter. Easy and user friendly



Built-in LED light mask



Brackets in line



Possibility to unlock motor with transmitter



Stylish design screwless at sight

## MODELS

	CODE	DESCRIPTION	PCS PALLET
29 <sub>N</sub>	RAY2524	For swing gates with maximum length 2,5 m and weight 250 kg, 24 Vdc motor (1 pc)	25
29.V	RAY4024	For swing gates with maximum length 4 m and weight 300 kg, 24 Vdc motor (1 pc)	25
24,0	RAY4024E	For swing gates with maximum length 4 m and weight 300 kg, 24 Vdc motor with encoder (1 pc)	25
	RAY40	For swing gates with maximum length 4 m and weight 300 kg, 230 Vac motor (1 pc)	25

TECHNICAL DATA		RAY2524	RAY4024	RAY4024E	RAY40
MECHANICAL DATA					
speed	cm/s	2,6	1,5	1,5	1,6
pulling force	N	1500	2000	2000	2000
working cycle	%	80	80	80	40
opening time at 90°	sec	adjustable	adjustable	adjustable	25
ELECTRICAL DATA					
control board		14AB	14AB2	14AB2	CT202
power	Vac (Vdc)	(24)	(24)	(24)	230
motor consumption	Α	3,5	5	5	1,2
absorbed power	W	85	120	120	280
capacitor	μF	-	-	-	8
thermoprotection	°C	-	-	-	150
integrated lights		yes	yes	yes	-
GENERIC DATA					
protection degree	IP	44	44	44	44
dimensions (L - P - H)	mm	844 - 100 - 104	844 - 100 - 104	844 - 100 - 104	844 - 100 - 10
weight	kg cad	6	8	8	8
working temperature	°C	-20 + 55	-20 + 55	-20 + 55	-20 + 55
leaves maximum weight	Kg	500	600	600	600

# LIMIT USE

2 2,5 3 3,5 4 Max gate length (m)

Gate shape and height and weather conditions can considerably reduce the values shown above, in the graph. 230 Vac motors are suggested for windy areas

## ACCESSORIES





PCS 2

PC 1



**ADRB** rear mounting brackets (only RAY2524)



PCS 2



**FCRAY** Pair of mechanical stops in closing

PCS 2

PC 1



ELS-C Horizontal 12 V

electrolock



PC 1



**KBP** 

PC 1

Battery back-up kit for 14A control unit

brackets

PCS 2



**KITFIXBATT** Fixing batteries

999LED Pair of led lights cold white

0 4 1 4 2 4 1 4 2 4 1 1 1 2 CHICK THE PROPERTY OF THE CO.

PCS 2



Unlock key cilinder



for outside opening



PC 1











RAY2524 (2 pcs) RAY 4024 (2 pcs) RAY40 (2 pcs)

## PLUS

Easy slowdown and open limit settings

Mechanical parts well protected from external agents

Opening mechanical stop included for proper gate installation and

New water resistant SUB remote control included

Night Light System with LED light included (24 Vdc version)

14A control unit (24 Vdc version)

	RAY KIT 24 Vo	RAY KIT 24 Vdc					
	CODE	DESCRIPTION	PCS PALLET				
9	KRAY2524ER	Kit for swing gates with leaves up to 2,5 m, 24 Vdc motor, control unit with slowdown and opening mechanic limit switch. With night light function included	15				
0	KRAY2524KR	Kit for swing gates with leaves up to 2,5 m, 24 Vdc motor, control unit with slowdown and opening mechanic limit switch	15				
9	KRAY4024ER	Kit for swing gates with leaves up to 4 m, 24 Vdc motor, control unit with slowdown and opening mechanic limit switch. With night light function included	15				
9	KRAY4024KR	Kit for swing gates with leaves up to 4 m, 24 Vdc motor, control unit with slowdown and opening mechanic limit switch	15				

RAY KIT 230 Vac			
CODE	DESCRIPTION	PCS PALLET	
KRAY42ER	Kit for swing gates with leaves up to 4 m, 230 Vac motor, control unit with slowdown and opening mechanic limit switch	15	
KRAY42KR	Kit for swing gates with leaves up to 4 m, 230 Vac motor, control unit with slowdown and opening mechanic limit switch	15	

## 24 Vdc KIT COMPONENTS















14A (1 pc) ECLIPSE (1 pc) RX4X (1 pc) FT32 (1 pc) SUB-44WR (1 pc) TS   KRAY2524ER • 14AB • • • • • • • • • • • • • • • • • • •								
KRAY2524KR ● 14AB		14A (1 pc)	ECLIPSE (1 pc)	RX4X (1 pc)	FT32 (1 pc)	SUB-44WR (1 pc)	SUB-44R (1 pc)	TS (1 pc)
KRAY4024ER ● <sub>14AB2</sub> ● ● ●	KRAY2524ER	• 14AB	•	•	•	•		•
ITABLE	KRAY2524KR	• 14AB		•	•		•	•
KRAY4024KR ● 14AB2 ● ●	KRAY4024ER	• 14AB2	•	•	•	•		•
	KRAY4024KR	• 14AB2		•	•		•	•

## 230 Vac KIT COMPONENTS















	CT202 (1 pc)	LUMY-230E (1 pc)	RX4X (1 pc)	FT32 (1 pc)	SUB-44WR (1 pc)	SUB-44R (1 pc)	TS (1 pc)
KRAY42ER	•	•	•	•	•		•
KRAY42KR	•		•	•		•	•

## ACCESSORIES





Pair of adjustable front mounting brackets (only RAY2524)

PCS 2

ADRB Pair of adjustable rear mounting brackets (only RAY2524)

PCS<sub>2</sub>



**FCRAY** Pair of mechanical stops in closing

PCS 2



ELS-C

PC 1

electrolock

Horizontal 12 V

PC1

**KBP** Battery back-up kit for 14A control unit

KITFIXBATT Fixing batteries brackets

999LED Pair of led lights cold white (for 24 Vdc)

CHIEFE CHIEF CONTROL

PCS 2

PCS 2



PC 1

Unlock key cilinder

**EXRB** Extentions bracket for outside opening

PC1

SEL-M Key selector, metal front, plastic back

PC 1



SEL-EU

Key selector with European cilinder, metal front and back PC 1

Warning board

PC1